

1310nm & 1550nm MQW-DFB Laser Diode with pigtail For 1.25G and 2.5G

Application

OSMDLP-XXXXXXXX



Features:

- ◆ Coaxial Package
- ◆ InGaAsP/InP MQW-DFB Laser Diode
- ◆ Low threshold, high slope efficiency and high output power LD
- ◆ Operating Case Temperature: -40°C to +85°C
- ◆ Single-mode fiber pigtailed with SC, FC, ST or LC connector
- ◆ Optional with Isolator

Applications:

- ◆ High Speed Optical Transmission System
- ◆ Test Equipments

General:

OSMDLP-XXXXXXXX Series are 1310nm & 1550nm InGaAsP/InP MQW-DFB laser diode modules designed for fiber optic communication systems. These modules have low threshold current and high performance at high temperature.

A laser diode is mounted into a coaxial package integrated with an InGaAs monitor PD and a single-mode pigtail.

Absolute Maximum Ratings: ^{*Note1}

Parameter	Symbol	Ratings	Unit
Storage Temperature	Tstg	-40~+100	°C
Operating Case Temperature	Top	-40~+85	°C
Forward Current (LD)	IfL	150	mA
Reverse Voltage (LD)	VrL	2	V
Reverse Voltage (PD)	VrP	15	V
Reverse Current (PD)	IrP	2	mA
Soldering Temperature (<10s)	Stemp	260	°C

*Note1: Exceeding any one of these values may destroy the device immediately.


Electrical and Optical Characteristics:

($P_o=2.5\text{mW}$, SMF, $T_c=+25^\circ\text{C}$, unless otherwise noted.)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Threshold Current	I _{th}	CW	—	10	15	mA
		CW, $T_c=-40\sim+85$	—	—	40	
Output Power (After coupled)	P _o	CW, I _f =I _{th} +20mA	1	2	2.5	mW
Operating Current	I _f	CW	—	30	40	mA
		CW, $T_c=-40\sim+85$	—	40	70	
Operating Voltage	V _f	CW, $T_c=-40\sim+85$	—	—	1.6	V
Slope Efficiency	Se	CW	0.05	—	0.15	mW/mA
Wavelength	λ_c	OSMDLP-3XXXXXX, CW	1290	1310	1330	nm
		OSMDLP-5XXXXXX, CW	1530	1550	1570	
Spectral Width	$\Delta\lambda$	CW, -20dB, $T_c=-40\sim+85$	—	—	1	nm
Side-mode suppression Ratio	SMSR	CW, $T_c=-40\sim+85$	30	—	—	dB
Tracking Error	ΔP_f	I _m hold(@ P _f =3mW(25°C)), CW, $T_c=-40\sim+85$	-1	—	1	dB
Relative Intensity Noise ^{*Note2}	RIN	CW	—	—	-145	dB/Hz
Monitor Current	I _m	CW, V _{rP} =5V, $T_c=-40\sim+85$	80	300	—	uA
Monitor Dark Current	I _d	CW, V _{rP} =5V	—	1	10	nA
Monitor Capacitance	C	V _{rP} =5V, f=1MHz	—	—	10	pF
Connector Repeatability	—		-1	—	1	dB
Optical Isolation	—	Single Stage	30	—	—	dB
		Dual Stage	40	—	—	

*Note2: Zero link loss, f=1780MHz

Pigtail Package Dimension: *Note3、 4、 5




*Note3: PIN direction and laser mark can be customized. Pigtail is standard SM fiber; the length also can be customized.

*Note4: For the package series D, the clamping rings dimensions (A) and drill size (B) are can be selected. The following types can be available. Please designate the detailed type while ordering the package series D.

Fixed card type	A(mm)	B(mm)
D	16	12
D-S	17	12.7


*Note5: For the package series B, the fix card is fixed by customer self. For the detailed information of fix card of A, C, D package series, please refers the following graphs.

The Direction of Fix Card:




Pin Assignment:

TYPE: 1



LD-pin-1 / TYPE: C

TYPE: 2



LD-pin-2 / TYPE: B

Nomenclature:

OSMDLP

A B C D E F G H

NO	Parameter	Detailed Description			
A	Wavelength	3=1310		5=1550	
B	Data Rate	1=1.25G		2=2.5G	
C	Power	05=0.3-0.8mw	10=0.81-1.8mw	20=1.81-2.5mw	
D	Package Series	A	B	C	E
E	Connector	F=FC/PC	S=SC/PC	T=ST/PC	L=LC/PC
		FA=FC/APC	SA=SC/APC	Blank=None	
F	Pin Type	Blank =LD-pin-2		1=LD-pin-1	
G	Isolator	Blank=None	G= Single Stage	G2=Dual Stage	
H	Fiber Type	Blank=SM			

Precaution:

- (1) The modules should be handled in the same manner as ordinary semiconductor devices to prevent the electro-static damages. For safe keeping and carrying, the modules should be packaged with ESD proof material. To assemble the modules on PCB, the workbench, the soldering iron and the human body should be grounded.
- (2) Please pay special attention to the atmosphere condition because the dew on the module may cause some electrical damages.
- (3) Under such a strong vibration environment as in automobile, the performance and reliability are not guaranteed.

Notice:

OSM reserves the right to make changes or discontinue any product or service identified in this publication, without notice, in order to improve design and/or performance. Applications that are described herein for any of the products are for illustrative purposes only. OSM makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.