

LC RFID Unibody Patch cord



The LC Unibody Series includes a jumper connector designed for 2.0mm duplex & 3.0mm simplex cables. The Unibody can be used for singlemode and multimode applications with either a PC or APC endface. Plastic housing and boot made from UL rated materials are also available. The series is compliant with Telcordia GR-326-CORE, IEC 61754-20, and TIA/EIA 604-10 standards, and meets independent testing criteria.

Features:

- ◆ Cable PVC, Hytrel, LSZH, OFNP, OFNR
- ◆ Cable Color Green, Yellow, Orange, Gray, Aqua or Customized Designs
- ◆ Singlemode and Multimode PC or 8 degree APC 9 degree APC
- ◆ Unibody Color Blue, Gray, Orange or White
- ◆ IP Addressable
- ◆ RFID Marked
- ◆ Prevents Overstretch
- ◆ Paperless Records

Application:

- ◆ Telecommunication
- ◆ CATV
- ◆ LAN & WAN
- ◆ Network
- ◆ Broadband
- ◆ FTTH

Performance Specifications:

Item	Type	PC	SPC	UPC	APC
Insertion Loss	SM	≤0.25dB	≤0.20dB	≤0.20dB	≤0.15dB
	MM	≤0.30dB	≤0.20dB	≤0.20dB	≤0.30dB
Return Loss	SM	≥45dB	≥50dB	≥55dB	≥65dB
	MM	≥35dB	≥35dB	≥35dB	≥35dB
Repetition Test		Additional Loss≤0.1dB, Return Loss Variability<5dB			
Temperature Stability(-20°C~85°C)		Additional Loss≤0.2dB, Return Loss Variability<5dB			
Storage Temperature		-40°C~+85°C			